
	PRODUCT SPECIFICATIONS	REF. No. : 614-02117XS1-02
	PRODUCT SERIES : Santak Castle Series MODEL : C10K-LCD TECHNOLOGY : Online double conversion	: B-WR1-235-217A : EN-00006-01
		Page No.: 1 OF 4

INPUT

Nominal Voltage	: 220VAC
Phase	: Single phase with ground (2W + G)
Power Factor	: ≥ 0.99
Voltage Range	: 120 ~ 275VAC
Volt. Low Detection / Comeback	: 120VAC / 140VAC, at load $\leq 50\%$; 150VAC / 165VAC, at $50\% < \text{load} \leq 70\%$; 165VAC / 180VAC, at $70\% < \text{load} \leq 90\%$; 185VAC / 200VAC, at load $> 90\%$;
Volt. High Detection / Comeback	: 275VAC / 260VAC, at load $0\% < \text{load} < 110\%$
Nominal Frequency	: 50/60Hz
Frequency Range	: 40 ~ 70Hz
Freq. Low Detection / Comeback	: 40Hz / 40.5Hz
Freq. High Detection / Comeback	: 70Hz / 69.5Hz
THDi	: $< 3\%$ (With R full load At Line normal)
Nominal RMS Current	: 44A
Protection	: 63Amp Breaker
Connection	: Terminal Block


BYPASS

Output before UPS power-on	: YES
Voltage Range	: 187 ~ 264VAC
Bypass Low Detection	: Default 187VAC, can be set to 187 ~ 228VAC through Winpower software
Bypass Low comeback	: Bypass Low voltage plus 10VAC
Bypass High detection	: Default 264VAC, can be set to 210 ~ 264VAC through Winpower software
Bypass High comeback	: Bypass High voltage minus 10VAC
Protection	: 63Amp Breaker
Auto transfer to bypass mode When UPS is overloaded, failed, low battery ...	

	PRODUCT SPECIFICATIONS	REF. No. : 614-02117XS1-02
	PRODUCT SERIES : Santak Castle Series MODEL : C10K-LCD TECHNOLOGY : Online double conversion	: B-WR1-235-217A : EN-00006-01
		Page No.: 2 OF 4

OUTPUT

Power Capacity	: 10kVA / 9kW
Power Factor	: 0.9
Voltage	: 220/230/240VAC
Voltage Regulation	: $\pm 1\%$
Waveform	: Sine wave
Voltage Distortion	: $\leq 2\%$ (linear load) $\leq 4\%$ (non-linear load))
Frequency	: Battery mode: 50/60Hz ± 0.2 Hz Line mode: Synchronized to 50/60Hz ± 4 Hz
Slew Rate	: < 1.0 Hz/sec
Phase Lock Error to Line	: $< 2^\circ$
Transient Recovery	: 60ms (R load from 90% to 110% and vice versa)
Current Crest Ratio	: 3:1
Efficiency	: Up to 90% at battery mode Up to 94% at line mode Up to 98% at ECO mode
Overload Capability	: 105%-125%, load transfer to bypass mode after 10 min (0-30°C) or 1 minutes (30-40°C); 125%-150%, load transfer to bypass mode after 30s; Over 150%, load transfer to bypass after 0.5s;
Nominal Output Current	: 45A
Short Circuit Protection	: Cut off output within 100ms in Line mode & Battery mode; Input Breaker in Bypass mode
Bypass Output without turning on	: Yes
Maintenance Bypass Switch	: Option
Connection	: Terminal Block


	PRODUCT SPECIFICATIONS	REF. No. : 614-02117XS1-02
	PRODUCT SERIES : Santak Castle Series MODEL : C10K-LCD TECHNOLOGY : Online double conversion	: B-WR1-235-217A : EN-00006-01
		Page No.: 3 OF 4

BATTERY AND CHARGER

Type	: VRLA, Maintenance Free
Rating	: 12V9Ah
Quantity	: 16 pieces
Nominal DC Voltage	: 192VDC
Backup Time	: 4 minutes at 100% load
Auto Shutdown Voltage	: 176VDC – 2VDC when load < 1kW 152VDC ± 2VDC when load > 1kW
Protection	: Fast-acting Fuse
Rated Charge Voltage	: 216VDC
Initial Charging Current	: 1.2A
Recharge Time	: 7 Hours recharge to 90%
Over Voltage Protection	: 235.2VDC (1 ± 1%)
Leakage Current	: < 0.5mA
Connection	: Built-in

INTERFACE

Control Panel	: Power On/Off, Self-test/Alarm silence
Indicators	: Graphical LED & LCD display: Line, Battery, Bypass, Inverter, Load level/Battery level, Fault
Diagnostics	: Full system self test on power up
Auto Restart Function	: Auto restart while AC source restored after discharge shutdown
DC Power-on Function	: On-battery power on
Audible Alarm	: Battery mode: Beeps every four seconds Battery low: Beeps every second Overload: Beeps twice every second Bypass: Beeps every two minutes Fault: Beeps continuously
Communications	
- DB-9 Port	: RS232 interface
- Intelligent Slot (SNMP)	: Available (Options : NMC, AS400 or CMC Card)
- Parallel Port	: Option
- Emergency Power Off(EPO)	: Option
Cooling	: Force air cooling

	PRODUCT SPECIFICATIONS	REF. No. : 614-02117XS1-02
	PRODUCT SERIES : Santak Castle Series MODEL : C10K-LCD TECHNOLOGY : Online double conversion	: B-WR1-235-217A : EN-00006-01
		Page No.: 4 OF 4

PARALLEL FUNCTION

Parallel card : Option
 Number of UPS in Parallel : Up to 3 units

TRANSFER TIME

Line mode <--> Battery mode : 0 ms
 Bypass mode <--> Line mode : 0 ms
 ECO mode to Line mode : < 4 ms
 Auto Transfer : Automatically re-transfer to Inverter mode after overload is cleared

ENVIRONMENTAL

Operating Temperature : 0 ~ 40°C
 Storage Temperature : -25°C ~ 55°C
 Humidity : 20% ~ 90%, Non-condensing
 Altitude : < 1000 m

STANDARD & SAFETY

Audible Noise : ≤ 50dB, at 1-meter distance in front of the front panel (Exclusive of Buzzer)
 EMC : IEC 61000
 IEC 2040-2
 Safety : IEC 62040-1

MECHANICAL FEATURES

Unit
 Dimensions (W x D x H) mm : 248 x 500 x 565 mm
 Weight (kg) : 62 kg
 Packaging
 Dimensions (W x D x H) mm : 380 x 680 x 834 mm
 Weight (kg) : 67.1 kg

Specifications are subject to change without notice.