

VALVE REGULATED LEAD ACID BATTERY - UPS TYPE





ABSORBENT GLASS MAT - AGM TECHNOLOGY

ECT-UP12100VA18 **12V100Ah**



Dimensions

mm



Specifications

Nominal Voltage(V) 12V

Nominal Capacity

10 hour rate	(10A	to	10.80V)	100Ah
5 hour rate	(17A	to	10.20V)	85Ah
1 hour rate	(60A	to	9.60V)	60Ah

Weight Approx. 31.3kg

Internal Resistance (at 1KHz) Approx. 4 mΩ

Maximum Discharge Current for

5 seconds: 1200A

Charging Methods at 25°C(77°F)

Cycle use:

Charging Voltage 14.4 to 15.0V

Coefficient -5.0mV/°C/cell

Maximum Charging Current 30A

Standby use:

Float Charging Voltage 13.50 to 13.80V

Coefficient -3.0mV/°C/cell

Operating Temperature Range

Charge -15°C(5°F) to 40°C(104°F)

Discharge -15°C(5°F) to 50°C(122°F)

Storage -15°C(5°F) to 40°C(104°F)

Design life 12 years

Charge Retention (shelf life) at 20°C(68°F)

1 month 98%

3 month 94%

6 month 85%

Case Material ABS UL94 HB

Option: Flammability resistance of (UL94 V-0)


Terminal F18

VALVE REGULATED LEAD ACID BATTERY - UPS TYPE


ABSORBENT GLASS MAT - AGM TECHNOLOGY

ECT-UP12100VA18 **12V100Ah**


Effect of Temperature on Capacity 25°C(77°F)




Trickle(or float) Service Life



Capacity Retention Characteristic



Cycle Service Life



- PERFORMANCE DATA

- Discharge Rates in Watts to Various End Voltages at 25°C (77°F)

End Voltage		1.85V	1.80V	1.75V	1.70V	1.65V	1.60V
Time							
10	min	342	370	397	414	433	465
15	min	285	315	345	358	373	383
20	min	250	272	299	303	319	333
30	min	207	222	230	234	235	238
60	min	123	132	140	141	143	145
180	min	49.9	53.2	55.2	55.6	56.7	58.2
300	min	33.4	35.5	37.3	37.7	38.0	38.3
600	min	18.8	19.2	19.3	19.7	20.0	20.2
1200	min	9.75	9.9	10.1	10.4	10.5	10.6

- Discharge Rates in Amperes to Various End Voltages at 25°C (77°F)

End Voltage		1.85V	1.80V	1.75V	1.70V	1.65V	1.60V
Time							
10	min	176	199	221	238	249	263
15	min	151	168	182	194	202	212
20	min	133	146	161	165	174	184
30	min	107	114	120	121	122	123
60	min	59.1	64.3	68.0	70.4	71.6	73.5
180	min	27.3	28.1	28.6	29.5	29.7	30.1
300	min	16.9	18.1	18.5	18.7	19.1	19.2
600	min	9.40	10.2	10.3	10.4	10.5	10.6
1200	min	5.05	5.16	5.22	5.43	5.49	5.54

All data on the spec. sheet is an average value:

THE TOLERANCE RANGE : X<6MIN(+15%~-15%), 6MIN<X<10MIN(+12%~-12%), 10MIN<X<60MIN(+8%~-8%), X≥60MIN(+5%~-5%)

Contents in this data sheet are subject to change for improvement without prior notice to users. For clarifications and updated information, please contact us.